



Statika nosivost za krovni panel

nominalna debljina	debljina lima	specifično opterećenje q (kN / m ²)				specifično opterećenje q (kN / m ²)			
									
d (mm)	δ1 / δ2 (mm)	1.00	1.25	1.50	1.75	1.00	1.25	1.50	1.75
30	0.4 / 0.4	2.75	2.70	2.60	2.30	3.50	3.20	2.95	2.80
	0.5 / 0.5	2.90	2.80	2.65	2.35	3.70	3.40	3.15	3.00
	0.6 / 0.6	3.05	2.90	2.75	2.40	3.90	3.60	3.35	3.20
	0.7 / 0.7	3.20	3.00	2.75	2.45	4.10	3.30	3.05	3.00
40	0.4 / 0.4	3.25	3.00	2.95	2.75	4.00	3.65	3.35	3.20
	0.5 / 0.5	3.40	3.10	3.05	2.85	4.20	3.85	3.55	3.40
	0.6 / 0.6	3.55	3.20	3.15	2.95	4.40	4.05	3.75	3.60
	0.7 / 0.7	3.70	3.30	3.20	3.05	4.60	4.25	4.00	3.80
50	0.4 / 0.4	3.55	3.05	3.30	2.90	4.20	3.90	3.70	3.50
	0.5 / 0.5	3.80	3.45	3.40	3.15	4.60	4.15	4.00	3.80
	0.6 / 0.6	4.05	3.75	3.50	3.40	5.00	4.45	4.30	4.10
	0.7 / 0.7	4.30	4.05	3.60	3.65	5.20	4.75	4.60	4.45
60	0.4 / 0.4	4.00	3.70	3.60	3.50	5.00	4.60	4.20	4.00
	0.5 / 0.5	4.20	3.80	3.75	3.60	5.20	4.80	4.40	4.20
	0.6 / 0.6	4.40	4.05	3.90	3.75	5.40	5.00	4.60	4.40
	0.7 / 0.7	4.60	4.30	4.05	3.90	5.60	5.20	4.80	4.60